

Package: waydown (via r-universe)

September 14, 2024

Type Package

Title Computation of Approximate Potentials for Weakly Non-Gradient Fields

Version 1.1.0

Author Pablo Rodríguez-Sánchez

Maintainer Pablo Rodríguez-Sánchez <pablo.rodriguez.sanchez@gmail.com>

Description Computation of approximate potentials for both gradient and non gradient fields. It is known from physics that only gradient fields, also known as conservative, have a well defined potential function. Here we present an algorithm, based on the classical Helmholtz decomposition, to obtain an approximate potential function for non gradient fields. More information in Rodríguez-Sánchez (2020) <doi:10.1371/journal.pcbi.1007788>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

URL <https://github.com/PabRod/waydown>

BugReports <https://github.com/PabRod/waydown/issues>

RoxygenNote 7.1.1

VignetteBuilder knitr

Suggests testthat, knitr, markdown, rmarkdown, deSolve, dplyr, colorRamps, ggplot2, gridExtra, latticeExtra, bindrcpp

Imports numDeriv, Matrix

Repository <https://pabrod.r-universe.dev>

RemoteUrl <https://github.com/pabrod/waydown>

RemoteRef HEAD

RemoteSha a6701c8a3bf3151c0e1f0bb5aa50cfe32362bc58

Contents

approxPot1D	2
approxPot2D	3
deltaV	4
Index	6

approxPot1D	<i>Approximate potential in one dimension</i>
-------------	---

Description

Approximate potential in one dimension

Usage

```
approxPot1D(f, xs, V0 = "auto")
```

Arguments

f	One-dimensional representing the flow (right hand side of differential equation)
xs	Vector of positions to evaluate
V0	(Optional) Value of V at first element of xs. When default, the global minimum is assigned 0

Value

The potential estimated at each point in xs

Author(s)

Pablo Rodríguez-Sánchez (<https://pabrod.github.io>)

References

<https://doi.org/10.1371/journal.pcbi.1007788>

See Also

[approxPot2D](#), [deltaV](#)

Examples

```
# Flow
f = function(x) { sin(x) }

# Sampling points
xs <- seq(0, 2*pi, length.out = 1e3)

# Approximated potential
Vs <- approxPot1D(f, xs)
```

approxPot2D*Approximate potential in two dimensions*

Description

Approximate potential in two dimensions

Usage

```
approxPot2D(f, xs, ys, V0 = "auto", mode = "mixed")
```

Arguments

f	Two-dimensional representing the flow (right hand side of differential equation)
xs	Vector xs positions to evaluate
ys	Vector of ys positions to evaluate
V0	(Optional) Value of V at first element of (xs,ys). When default, the global minimum is assigned 0
mode	(Optional) Integration mode. Options are horizontal (default), vertical and mixed

Value

The potential estimated at each point (xs, ys)

Author(s)

Pablo Rodríguez-Sánchez (<https://pabrod.github.io>)

References

<https://doi.org/10.1371/journal.pcbi.1007788>

See Also

[approxPot1D](#), [deltaV](#)

Examples

```
# Flow
f = function(x) {c(-x[1]*(x[1]^2 - 1.1), -x[2]*(x[2]^2 - 1))}

# Sampling points
xs <- seq(-1.5, 1.5, length.out = 10)
ys <- seq(-1.5, 1.5, length.out = 15)

# Approximated potential
Vs <- approxPot2D(f, xs, ys, mode = 'horizontal')
```

deltaV

Approximate potential difference between two points

Description

Approximate potential difference between two points

Usage

```
deltaV(f, x, x0, normType = "f")
```

Arguments

f	Flow equations (right hand side of differential equation)
x	Position where we want to know the approximate potential
x0	Reference position (center of the Taylor expansion)
normType	(default: 'f') Matrix norm used to compute the error

Value

A list containing the approximate potential difference between x and x0 and the estimated error

Author(s)

Pablo Rodríguez-Sánchez (<https://pabrod.github.io>)

References

<https://doi.org/10.1371/journal.pcbi.1007788>

See Also

[approxPot1D](#), [approxPot2D](#), [norm](#)

Examples

```
# One dimensional flow
f <- function(x) { cos(x) }

# Evaluation points
x0 <- 1
x1 <- 1.02

dV <- deltaV(f, x1, x0)

# Two dimensional flow
f <- function(x) { c(
  -2*x[1]*x[2],
  -x[1]^2 - 1
)}

# Evaluation points
x0 <- matrix(c(1,2), ncol = 1)
x1 <- matrix(c(0.98,2.01), ncol = 1)

dV <- deltaV(f, x1, x0)
```

Index

`approxPot1D`, [2](#), [3](#), [4](#)

`approxPot2D`, [2](#), [3](#), [4](#)

`deltaV`, [2](#), [3](#), [4](#)

`norm`, [4](#)